## NSN 5910-00-106-1286

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-106-1286

**Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.200 inches **Body Width:** 0.200 inches **Body Height:** 0.100 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.200 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 330.000 picofarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -15.0/+15.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.5000 **Terminal Surface Treatment:** Solder **Test Data Document:** 

90056-8-11-06481 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-106-1286

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:
-------------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0