

View Online at https://aerobasegroup.com/nsn/5910-00-106-3849

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

# **Terminal Length:**

1.250 inches

**Body Length:** 

0.190 inches

#### **Body Width:**

0.190 inches

**Body Height:** 

0.090 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

### **Capacitance Value Per Section:**

39.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Ceramic

### Insulation Resistance At Reference Temp:

100000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

### **Terminal Surface Treatment:**

Solder

### **Test Data Document:**

81349-milc39014/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0