

View Online at <https://aerobasegroup.com/nsn/5910-00-106-5028>

Body Style:

W/o mtg facilities terminal (s) on one surface

Mil-std-1276 Wire Lead Type Designator:

N-1

Reliability Indicator:

Not established

Terminal Length:

1.000 inches

Body Length:

0.275 inches

Body Width:

0.286 inches

Body Height:

0.156 inches

Center To Center Distance Between Terminals Parallel To Length:

0.150 inches

Terminal Diameter:

0.016 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Nonpolarized

Capacitance Value Per Section:

7.500 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

51.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dc Leakage At Reference Temp:

2.300 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0