

View Online at <https://aerobasegroup.com/nsn/5910-00-106-5028>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Mil-std-1276 Wire Lead Type Designator:**

N-1

**Reliability Indicator:**

Not established

**Terminal Length:**

1.000 inches

**Body Length:**

0.275 inches

**Body Width:**

0.286 inches

**Body Height:**

0.156 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.150 inches

**Terminal Diameter:**

0.016 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Nonpolarized

**Capacitance Value Per Section:**

7.500 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

51.0 milliamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

15.0 dc single section

**Tolerance Range Per Section:**

-20.00 to 20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dc Leakage At Reference Temp:**

2.300 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0