

View Online at <https://aerobasegroup.com/nsn/5910-00-107-2660>

**Body Style:**

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:**

Not established

**Terminal Length:**

0.875 inches

**Body Length:**

0.500 inches

**Body Width:**

0.094 inches

**Body Height:**

0.500 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Nimitz class cvn, tarawa class lha, wasp class lhd, powhatan class t-atf 166, communications, lha, emory s. Land class as, toiconderoga class cg (47), arleigh burke class ddg, forrestal class cv. Countermeasures set (an/ulq-19).

**Capacitance Value Per Section:**

39.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-15.0/+15.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

2500.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:**

Glass

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.1000

**Terminal Surface Treatment:**

Silver

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 ribbon

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0