

View Online at <https://aerobasegroup.com/nsn/5910-00-107-2660>

Body Style:

W/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Not established

Terminal Length:

0.875 inches

Body Length:

0.500 inches

Body Width:

0.094 inches

Body Height:

0.500 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Nimitz class cvn, tarawa class lha, wasp class lhd, powhatan class t-atf 166, communications, lha, emory s. Land class as, toiconderoga class cg (47), arleigh burke class ddg, forrestal class cv. Countermeasures set (an/ulq-19).

Capacitance Value Per Section:

39.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

2500.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Glass

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.1000

Terminal Surface Treatment:

Silver

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 ribbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0