## NSN 5910-00-109-4455

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-109-4455 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.455 inches **Body Length:** 2.263 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 230.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Criticality Code Justification:** Feat **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 10.0000 **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Special Features:** 

Design analysis

**Nuclear Hardness Critical Feature:** 

Hardened

## NSN 5910-00-109-4455

Electrolytic Fixed Capacitor - Page 2 of 2



## **Test Data Document:**

94756-441-0380 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A010b0