

View Online at <https://aerobasegroup.com/nsn/5910-00-109-9258>

**Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Mil-std-1276 Wire Lead Type Designator:**

N-1n-1n-1

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

1.000 inches 1.000 inches 1.000 inches

**Body Diameter:**

0.082 inches

**Body Length:**

0.355 inches

**Terminal Diameter:**

Between 0.014 inches and 0.018 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Nonpolarized

**Capacitance Value Per Section:**

2.300 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

18.8 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

6.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

10.000

**Dc Leakage At Reference Temp:**

1.500 microamperes

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0