NSN 5910-00-110-0393

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-110-0393					
Body Style:					
W/o mtg facilities, terminals on opposite surfaces					
Reliability Indicator:					
Not established					
Unable To Decode:					
Unable to decode and					
Terminal Length:					
1.500 inches					
Body Length:					
Between 0.789 inches and 0.851 inches					
Body Width:					
Between 0.280 inches and 0.300 inches					
Body Height:					
Between 0.410 inches and 0.430 inches					
Terminal Diameter:					
0.025 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Insulation Resistance At Maximum Operating Temp:					
100.0 megohm-microfarads					
Capacitance Value Per Section:					
0.750 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 85.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
100.0 dc single section					
Tolerance Range Per Section:					
-5.00 to 5.00 percent single section					
Case Material:					
Plastic					
Insulation Resistance At Reference Temp:					
10000.0 megohm-microfarads					
Dissipation Factor At Reference Tempurature In Percent:					
1.000					
Terminal Surface Treatment:					
Solder					
Dielectric Material:					
Plastic polyethylene terephthalate					
Terminal Type And Quantity:					
2 uninsulated wire lead					

N/a

Shelf Life:

NSN 5910-00-110-0393

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



ш	Inıŧ	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A010b0