Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-110-7329

### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

# Body Diameter:

0.312 inches

### **Body Length:**

1.030 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

### Anode Type:

Plain foil

### **Electrical Polarization:**

Polarized

# Capacitance Value Per Section:

1.000 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

# **Tolerance Range Per Section:**

-15.00 to 15.00 percent single section

#### Case Material:

Metal

# **Capacitive Electrode Material:**

Tantalum

# Power Factor At Reference Tempurature In Percent:

2.0000

A010b0

# Test Data Document:

81349-mil-c-3965/15 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: