Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-110-7334

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Body Diameter:

0.219 inches

Body Length:

0.812 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Etched foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

10.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-15.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Tempurature In Percent:

2.0000

Test Data Document:

81349-mil-c-3965/17 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A010b0