

View Online at <https://aerobasegroup.com/nsn/5910-00-110-9196>

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.364 inches

Body Length:

1.275 inches

Body Width:

0.783 inches

Body Height:

1.375 inches

Center To Center Distance Between Terminals Parallel To Length:

0.624 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Nonpolarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-15.00 to 75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Temperature In Percent:

2.0000

Dc Leakage At Reference Temp:

42.000 microamperes

Test Data Document:

81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-c-3965/12 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0