Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-110-9293

# **Body Style:**

W/o mtg facilities terminal (s) on one surface

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.000 inches

# Body Length:

0.685 inches

### **Body Width:**

0.670 inches

#### **Body Height:**

### 0.195 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.600 inches

### **Terminal Diameter:**

0.025 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

# **Capacitance Value Per Section:**

33000.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-900.0/+900.0 single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

# **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

## **Terminal Surface Treatment:**

Solder

## **Dielectric Material:**

Plastic

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0