Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-112-7099

### **Body Style:**

W/o mtg facilities, terminal (s) on one surface

### **Reliability Indicator:**

Not established

# **Body Length:**

2.500 inches

#### **Body Width:**

1.188 inches

# **Body Height:**

2.875 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.938 inches and 1.187 inches

**Terminal Height From Body:** 

1.750 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## Capacitance Value Per Section:

0.500 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

### Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 threaded stud

### Shelf Life:

N/a

### Unit Of Measure:

Paper Dielectric Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

