NSN 5910-00-112-7436

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-112-7436

| Body Style: |
|---|
| W/o mtg facilities, terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 1.188 inches |
| Body Height: |
| 4.750 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| Between 0.938 inches and 1.187 inches |
| Terminal Height From Body: |
| 1.375 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Hermetically sealed case |
| Insulation Resistance At Maximum Operating Temp: |
| 150.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 6.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 600.0 dc single section |
| Tolerance Range Per Section: |
| -10.00 to 10.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 1500.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Test Data Document: |
| 81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5910-00-112-7436

Paper Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0