

View Online at https://aerobasegroup.com/nsn/5910-00-112-7588

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

# **Body Diameter:**

1.062 inches

#### **Body Length:**

1.438 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Features Provided:

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

600.0 megohms

### **Capacitance Value Per Section:**

6000.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc single section

# **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

6000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

**Terminal Surface Treatment:** 

Solder

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

### Shelf Life:

N/a

Unit Of Measure:

Paper Dielectric Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

