NSN 5910-00-112-7619

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-112-7619

3 · · · · · · · · · · · · · · · · · · ·	
Body Style:	
W/o mtg facilities, axial terminals	
Reliability Indicator:	
Not established	
Terminal Length:	
1.500 inches	
Body Diameter:	
0.687 inches	
Body Length:	
1.687 inches	
Body Width:	
0.687 inches	
Body Height:	
0.687 inches	
Terminal Diameter:	
0.040 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Internal Electrical Connection Type:	
Inserted tab	
Features Provided:	
Hermetically sealed case	
Insulation Resistance At Maximum Operating Temp:	
20.0 megohm-microfarads	
Capacitance Value Per Section:	
50000.000 picofarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 85.0 degrees celsius	
Nonderated Continuous Voltage Rating And Type Per Sect	ion:
600.0 dc single section	
Tolerance Range Per Section:	
-10.00 to 10.00 percent single section	
Case Material:	
Metal	
Insulation Resistance At Reference Temp:	
2000.0 megohm-microfarads	
Dissipation Factor At Reference Tempurature In Percent:	
1.0000	
Terminal Surface Treatment:	
Solder	

Plastic

Case Insulation Material:

NSN 5910-00-112-7619

Paper Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/2b government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0