## NSN 5910-00-113-1236



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-113-1236 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.219 inches **Body Length:** 0.875 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 892.0 **Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 2.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 3.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -20.00 to 20.00 percent single section **Case Material:** Metal

**Capacitive Electrode Material:** 

Tantalum

Dc Leakage At Reference Temp:

1.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Reference Number Differentiating Characteristics:** 

As differentiated by navord od41152

## NSN 5910-00-113-1236

Electrolytic Fixed Capacitor - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0