Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-113-2631

# **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.219 inches

#### **Body Length:**

0.578 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Solid

# Impedance At Minimum Operating Tempurature In Ohms:

# 155.0

**Electrical Polarization:** 

Polarized

#### **Capacitance Value Per Section:**

15.000 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

2.0 milliamperes

# Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Aluminum

# Equivalent Series Resistance At Reference Tempurature In Ohms:

5.00

### Dc Leakage At Reference Temp:

1.000 microamperes

# **Case Insulation Material:**

Plastic

#### **Test Data Document:**

81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-00-113-2631

Electrolytic Fixed Capacitor - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0