Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-113-4951

#### **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.406 inches

#### Body Length:

1.562 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Plain foil

#### **Electrical Polarization:**

Polarized

### Capacitance Value Per Section:

7.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### Case Material:

Metal

## **Capacitive Electrode Material:**

Tantalum

## Power Factor At Reference Tempurature In Percent:

2.0000

A010b0

## Test Data Document:

81349-mil-c-3965/15 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: