

View Online at <https://aerobasegroup.com/nsn/5910-00-115-3601>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

0.281 inches 0.281 inches 0.281 inches

Body Diameter:

Between 2.969 inches and 3.031 inches

Body Length:

Between 5.563 inches and 5.687 inches

Continuous Current Rating In Amps:

13.4

Center To Center Distance Between Terminals Parallel To Diameter:

Between 1.234 inches and 1.266 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

1.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

21500.000 picofarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 65.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

45.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.054

Dc Leakage At Reference Temp:

2.000 microamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0