## NSN 5910-00-115-8407

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-115-8407

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
1.375 inches
Body Width:
0.783 inches
Body Height:
2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.374 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Etched foil
Impedance At Minimum Operating Tempurature In Ohms:
4.0
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
700.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-15.00 to 75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
73000.000 milliamperes
Test Data Document:
81349-mil-c-3965/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life: N/a

2 tab, solder lug

**Terminal Type And Quantity:** 

## NSN 5910-00-115-8407

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0