NSN 5910-00-116-2642

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-116-2642

| Body Style: |
|---|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 2.500 inches 2.500 inches 2.500 inches |
| Body Diameter: |
| 0.937 inches |
| Body Length: |
| 2.750 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Anode Type: |
| Plain foil |
| Impedance At Minimum Operating Tempurature In Ohms: |
| 2.5 |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 300.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 75.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+50.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5910-00-116-2642

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0