

View Online at <https://aerobasegroup.com/nsn/5910-00-116-8965>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.485 inches

Bushing Diameter:

0.120 inches

Bushing Length:

0.219 inches

Body Length:

0.266 inches

Overall Diameter:

0.140 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-0.0 to 100.0 single section

Quality Factor At 25 Deg Celsius:

500.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

80

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.120 inches

Capacitance Range In Picofarads:

+0.5 to 7.5 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.04 single section

Test Data Document:

13499-922-0585-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0