NSN 5910-00-117-2630

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-117-2630

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.495 inches and 0.515 inches **Body Length:** 1.125 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohm-microfarads **Capacitance Value Per Section:** 5.600 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 100000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Surface Treatment:** Solder **Test Data Document:** 18876-mis16273 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

Shelf Life:

Onon Life.

N/a

Unit Of Measure:

2 uninsulated wire lead

--

NSN 5910-00-117-2630

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0