Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-118-1219

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.000 inches

## **Body Length:**

0.560 inches

### **Body Width:**

0.672 inches

### **Body Height:**

0.100 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.350 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

## Capacitance Value Per Section:

680.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

+0.0 to 70.0 single section

## **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

## Case Material:

Plastic

## Insulation Resistance At Reference Temp:

100000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.0007

## **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0