NSN 5910-00-118-8149



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5910-00-118-8149
Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
1.812 inches
Body Width:
1.062 inches
Body Height:

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches

3.750 inches

Terminal Height From Body:

0.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.406 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.906 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting holes

Capacitance Value Per Section:

0.900 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

1800.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Power Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

NSN 5910-00-118-8149

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

1 standoff, solder lug and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0