

View Online at <https://aerobasegroup.com/nsn/5910-00-118-9956>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.187 inches

Terminal Length:

Between 0.220 inches and 0.280 inches

Body Length:

0.359 inches

Terminal Diameter:

0.051 inches

Schematic Diagram Designator:

Feedthrough

End Application:

Defense support program, aircraft, hercules c-130f, tarawa class lha

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

1000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-33.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-20.00/+50.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

3.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 uninsulated wire lead and 1 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0