Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-120-1678

Body Style:

W/thd bushing mtg, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

1.000 inches

Body Diameter:

1.500 inches

Body Length:

5.250 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware and hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

4.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.750 inches

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 threaded stud

Shelf Life:

N/a

Paper Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0