## NSN 5910-00-121-3954

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-121-3954

**Body Style:** W/mtg tabs/flanges, terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.188 inches **Body Length:** 1.750 inches **Body Width:** 1.250 inches **Body Height:** 0.750 inches **Center To Center Distance Between Terminals Parallel To Length:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.375 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Type And Quantity:** 2 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 2.200 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 250.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 450.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

1.0000

**Power Factor At Reference Tempurature In Percent:** 

NSN 5910-00-121-3954 Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0