## NSN 5910-00-121-4873

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-121-4873

| Body Style:   |
|---|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator:  |
| Not establishednot established  |
| Body Diameter:  |
| 0.185 inches  |
| Body Length:  |
| 0.510 inches  |
| Schematic Diagram Designator:   |
| Electrod (s) grounded to case, w/gnd terminal   |
| Anode Type:   |
| Solid   |
| Electrical Polarization:  |
| Polarized   |
| Features Provided:  |
| Hermetically sealed case  |
| Capacitance Value Per Section:  |
| 2.200 microfarads single section  |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 85.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 35.0 dc single section  |
| Tolerance Range Per Section:  |
| -10.00/+10.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Tantalum  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A010b0  |