NSN 5910-00-121-6349

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-121-6349

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.571 inches
Body Width:
0.260 inches
Body Height:
0.409 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
250.0 dc single section
200.0 do single section
Tolerance Range Per Section:
-
Tolerance Range Per Section:
Tolerance Range Per Section: -10.00/+10.00 percent single section
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity: 2 uninsulated wire lead
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Dielectric Material: Plastic polypropylene Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: