NSN 5910-00-123-5217

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-123-5217
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.750 inches
Body Length:
0.250 inches
Body Width:
0.100 inches
Body Height:
0.100 inches
Terminal Diameter:
Between 0.069 inches and 0.131 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.200 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -150.0 single section
-150.0 single section
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 7500.0 megohms
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 7500.0 megohms Dissipation Factor At Reference Tempurature In Percent:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 7500.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 7500.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500 Terminal Surface Treatment:
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 7500.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500 Terminal Surface Treatment: Solder
-150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -60.0/+60.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 7500.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500 Terminal Surface Treatment: Solder Terminal Type And Quantity:

--

Unit Of Measure:

NSN 5910-00-123-5217

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A010b0