NSN 5910-00-123-5700

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-123-5700 **Body Style:** Rotary **Terminal Length:** 0.055 inches **Overall Height:** 0.125 inches **Overall Diameter:** 0.250 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -150.0 to 150.0 single section **Quality Factor At 25 Deg Celsius:** 100.0 **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +1.6 to 9.0 single section **Nonderated Voltage Rating And Type:** 50.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.75 single section **Special Features:** Terminal mtd **Test Data Document:** 07187-2504812-16 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a

--

Unit Of Measure:

NSN 5910-00-123-5700

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0