## NSN 5910-00-123-9964

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-123-9964

**Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Body Diameter:** 1.031 inches **Body Length:** 2.750 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Mounting Facility Screw Thread Series Designator:** Unc **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 0.220 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.164 inches Nonderated Continuous Voltage Rating And Type Per Section: 2000.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Ceramic **Insulation Resistance At Reference Temp:** 25000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic **Test Data Document:** 

81349-mil-c-19978/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 solder stud

## NSN 5910-00-123-9964

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| SI | 1e  | lf  | Ιi | fe: |
|----|-----|-----|----|-----|
| Ο. | ··· | ••• | _, | ٠٠. |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0