## NSN 5910-00-124-5018

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-124-5018

| Body Style:   |
|---|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 1.500 inches 1.500 inches 1.500 inches  |
| Body Diameter:  |
| 0.375 inches  |
| Body Length:  |
| 0.812 inches  |
| Schematic Diagram Designator:   |
| Electrod (s) grounded to case, w/gnd terminal   |
| Anode Type:   |
| Plain foil  |
| Electrical Polarization:  |
| Polarized   |
| Capacitance Value Per Section:  |
| 35.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -20.0 degrees celsius and 85.0 degrees celsius  |
| Dc Leakage At Maximum Operating Temp:   |
| 9.9 milliamperes  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 50.0 dc single section  |
| Tolerance Range Per Section:  |
| -10.00/+75.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Aluminum  |
| Terminal Surface Treatment:   |
| Solder  |
| Case Insulation Material:   |
| Plastic   |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

No

Demilitarization:

## NSN 5910-00-124-5018

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0