

View Online at <https://aerobasegroup.com/nsn/5910-00-128-0411>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

4.000 inches

Body Width:

2.375 inches

Body Height:

2.875 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

11.0

Highest Frequency At Which Rf Current Rating Applies In Kilohertz:

300.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

2.5

Lowest Frequency At Which Rf Current Rating Applies In Kilohertz:

100.0

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.562 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.625 inches

Mounting Facility Type And Quantity:

3 unthreaded mounting holes

Capacitance Value Per Section:

2000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Plastic

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0