

View Online at <https://aerobasegroup.com/nsn/5910-00-128-7774>

**Body Style:**

Rotary

**Body Length:**

1.219 inches

**Body Width:**

0.706 inches

**Body Height:**

0.938 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

-500.0 single section

**Unthreaded Mounting Hole Diameter:**

0.112 inches and 0.112 inches

**Dissipation Factor At 25 Deg Celsius In Percent:**

0.2

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.656 inches

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encapsulated

**Adjustment Device Rotation:**

360.0 degrees clockwise

**Adjustment Device Torque:**

Between 0.250 inch-ounces and 2.750 inch-ounces

**Insulation Dc Resistance At 25 Deg Celsius:**

10000.0 megohms

**Mounting Facility Type And Quantity:**

2 threaded hole

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.112 inches

**Capacitance Range In Picofarads:**

+20.0 to 125.0 single section

**Nonderated Voltage Rating And Type:**

500.0 dc continuous single section

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

-1.00 to 6.50 and -4.00 to 1.00 single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.50 single section

**Special Features:**

Mtg holes tapped 0.188 in.Deep

**Material:**

Steatite base

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0