

View Online at <https://aerobasegroup.com/nsn/5910-00-128-7774>

Body Style:

Rotary

Body Length:

1.219 inches

Body Width:

0.706 inches

Body Height:

0.938 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-500.0 single section

Unthreaded Mounting Hole Diameter:

0.112 inches and 0.112 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.2

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.656 inches

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encapsulated

Adjustment Device Rotation:

360.0 degrees clockwise

Adjustment Device Torque:

Between 0.250 inch-ounces and 2.750 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 threaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.112 inches

Capacitance Range In Picofarads:

+20.0 to 125.0 single section

Nonderated Voltage Rating And Type:

500.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-1.00 to 6.50 and -4.00 to 1.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Special Features:

Mtg holes tapped 0.188 in.Deep

Material:

Steatite base

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0