

View Online at https://aerobasegroup.com/nsn/5910-00-131-1183

## **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

## **Body Diameter:**

0.875 inches

**Body Length:** 

0.156 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.355 inches and 0.395 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

1000.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-2200.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-400.0/+400.0 single section

## **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

10000.0 megohms

### **Quality Factor At Reference Temp:**

1000.0000

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-131-1183

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

