NSN 5910-00-132-3504

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-132-3504

View Online at https://aerobasegroup.com/nsn/5910-00-132-3504
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
2.000 inches
Body Diameter:
0.813 inches
Body Length:
1.875 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
50.000 microfarads single section
Nonderated Operating Temp:
Between -25.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
150.0 dc single section
Tolerance Range Per Section:
-10.00 to 75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
12.0000
Dc Leakage At Reference Temp:
126.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
03545-mfd115t50 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-00-132-3504

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0