NSN 5910-00-132-5994

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-132-5994

Body Style:	
V/o mtg facilities, axial terminals	
Reliability Indicator:	
Not established	
Ferminal Length:	
.500 inches	
Body Diameter:	
0.383 inches	
Body Length:	
2.860 inches	
Schematic Diagram Designator:	
Electrod (s) grounded to case, w/gnd terminal	
Anode Type:	
Plain foil	
mpedance At Minimum Operating Tempurature In Ohms:	
25.0	
Electrical Polarization:	
Polarized	
Capacitance Value Per Section:	
20.000 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 85.0 degrees celsius	
Oc Leakage At Maximum Operating Temp:	
30.0 milliamperes	
Nonderated Continuous Voltage Rating And Type Per Section:	
75.0 dc single section	
Tolerance Range Per Section:	
10.00/+30.00 percent single section	
Case Material:	
Metal .	
Capacitive Electrode Material:	
Aluminum	
Dissipation Factor At Reference Tempurature In Percent:	
5.0000	
Oc Leakage At Reference Temp:	
0.000 microamperes	
Ferminal Surface Treatment:	
Solder	
Case Insulation Material:	
Plastic	
Fest Data Document:	

81349-mil-c-39018+1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-00-132-5994

Electrolytic Fixed Capacitor - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0