

View Online at <https://aerobasegroup.com/nsn/5910-00-133-8594>

Body Style:

W/thd mtg hol (s)/stud(s) terminals on one surface

Reliability Indicator:

Not established

Terminal Length:

2.000 inches

Body Length:

2.251 inches

Body Width:

1.875 inches

Body Height:

0.500 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

7.15

Highest Frequency At Which Rf Current Rating Applies In KiloHertz:

30.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

3.4

Lowest Frequency At Which Rf Current Rating Applies In KiloHertz:

12.0

Terminal Diameter:

0.064 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.983 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.607 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

200.500 microfarads 3rd section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 150.0 degrees celsius

Thread Size:

0.086 inches

Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 ac-peak all sections

Temperature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-20.0 to 100.0 single section

Tolerance Range Per Section:

-1.00 to 1.00 percent 4th section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Quality Factor At Reference Temp:

10000.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

4 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0