NSN 5910-00-134-9699

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-134-9699

| D - | ٠. د | C4 | ٠ |
|------------|------|-----|-----|
| DU | uv | Stv | ıe: |

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.063 inches 0.063 inches 0.063 inches

Body Diameter:

2.563 inches

Body Length:

3.500 inches

Center To Center Distance Between Terminals Parallel To Diameter:

1.125 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Impedance At Minimum Operating Tempurature In Ohms:

4.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

5500.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

7.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

40.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.052

Dc Leakage At Reference Temp:

4.000 milliamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded stud

NSN 5910-00-134-9699

Electrolytic Fixed Capacitor - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0