# NSN 5910-00-135-4370

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-135-4370

# **Body Style:**

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

### **Reliability Indicator:**

Not establishednot established

### **Terminal Length:**

Between 0.250 inches and 0.250 inches and 0.250 inches and 0.312 inches 0.312 inches

# **Body Diameter:**

Between 3.000 inches and 3.094 inches

# **Body Length:**

Between 4.125 inches and 4.563 inches

#### **Center To Center Distance Between Terminals Parallel To Diameter:**

Between 1.187 inches and 1.313 inches

#### **Terminal Diameter:**

0.190 inches

### **Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

### **Anode Type:**

Plain foil

# **Impedance At Minimum Operating Tempurature In Ohms:**

\_ .

# **Electrical Polarization:**

Polarized

# Capacitance Value Per Section:

4500.000 microfarads single section

# **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

### **Case Material:**

Metal

# **Capacitive Electrode Material:**

Aluminum

### **Case Insulation Material:**

Plastic

# **Terminal Type And Quantity:**

2 threaded hole

# Shelf Life:

N/a

### **Unit Of Measure:**

--

# NSN 5910-00-135-4370

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0