

View Online at <https://aerobasegroup.com/nsn/5910-00-136-4058>

Thread Class:

2a

Body Style:

Piston

Bushing Diameter:

0.216 inches

Bushing Length:

0.260 inches

Body Length:

0.740 inches

Overall Diameter:

0.240 inches

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Quality Factor At 25 Deg Celsius:

800.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 8.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1000.0 gigohms

Bushing Width:

0.193 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

28

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.216 inches

Capacitance Range In Picofarads:

+0.8 to 16.0 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Test Data Document:

18876-10658228 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0