NSN 5910-00-138-1252



Air Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-138-1252 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.750 inches **Bushing Diameter:** 0.234 inches **Bushing Length:** 0.172 inches **Body Length:** 0.500 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Quality Factor At 25 Deg Celsius:** 3000.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encapsulated **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 1.000 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.234 inches

Capacitance Range In Picofarads:

+1.0 to 20.0 single section

NSN 5910-00-138-1252

Air Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Precious Material And Location: Exterior metal parts except bushing gold Precious Material: Gold Terminal Type And Quantity: 1 tab, solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization:

No Fiig: A096a0