NSN 5910-00-138-1395

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-138-1395 |
|--|
| Body Style: |
| W/o mtg facilities, terminal (s) on one end |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 3.062 inches |
| Body Length: |
| 6.000 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Impedance At Minimum Operating Tempurature In Ohms: |
| 1.9 |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 4700.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 150.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+75.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 20.0000 |
| Dc Leakage At Reference Temp: |
| 1260.000 microamperes |
| Case Insulation Material: |
| Plastic |
| Test Data Document: |
| 81349-milc62/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 threaded hole |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5910-00-138-1395

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0