NSN 5910-00-139-6677

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-139-6677

| Body Style: |
|---|
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 2.250 inches |
| Body Diameter: |
| 0.406 inches |
| Body Length: |
| 0.891 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Impedance At Minimum Operating Tempurature In Ohms: |
| 60.0 |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 56.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 75.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Tantalum |
| Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 6.00 |
| Dc Leakage At Reference Temp: |
| 2.100 microamperes |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Test Data Document: |
| 95542-908230 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |

N/a

Shelf Life:

2 uninsulated wire lead

NSN 5910-00-139-6677

Electrolytic Fixed Capacitor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0