NSN 5910-00-139-6719

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-139-6719

view Offilite at https://aerobasegroup.com/hsh/55/10-00-155-07/15
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
2.250 inches
Body Diameter:
0.406 inches
Body Length:
0.891 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
45.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
82.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-20.00 to 20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Equivalent Series Resistance At Reference Tempurature In Ohms:
4.00
Dc Leakage At Reference Temp:
2.050 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
95542-908230 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-00-139-6719

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0